

VAPRO AVANCER SSL 15W-40

SN

SEMI SYNTHETIC ENGINE OIL

DESCRIPTION

VAPRO AVANCER SSL 15W-40 Semi synthetic motor oil advanced formulation fortified with most effective additives and blended using latest technology for most demanding modern high-performance engines.

APPLICATION

Suitable for all gasoline, diesel, gas or duel fuel engines of passenger cars, light duty commercial vehicles, and off-road SUV's requiring API SN viscosity grade or as recommended by the OEM. It helps lower the maintenance cost by keeping your engine clean providing reduced engine wear and improving performance.

PERFORMANCE FEATURES AND BENEFITS

- Semi Synthetic formulation.
- Improved Oxidation resistance.
- Protection from piston deposits
- Superior wear and corrosion protection.
- Excellent fuel economy and energy efficiency.
- Longer drain intervals and smooth running of engines.
- Helps quick cold weather starting.

SPECIFICATIONS AND APPROVALS

- ACEA A3/B3
- MB 229.1
- VW 501.01/505.00
- BMW LL-98
- RN-0700
- GM LL-A-025
- API SN

TYPICAL PHYSICAL CHARACTERISTICS

VAPRO AVANCER SSL	METHOD	TYPICAL RESULTS
SAE Viscosity Grade	SAE	15W-40
Density @ 15°C kg/l		0.875
Kinematic Viscosity @ 40°C cSt	ASTM D 445	105.0
@ 100°C cSt	ASTM D 445	14.5
Viscosity Index	ASTM D 2270	142
Flash point °C	ASTM D 92	230
Pour point °C	ASTM D 97	-33
Total Base Number	ASTM D 2896	10.5

These characteristics are typical of current production. Whilst future production will conform to Vapro's specification, variations in these characteristics may occur.