



VAPRO SINERGIA FSL 0W-30

SN/CF

FULLY SYNTHETIC ENGINE OIL

DESCRIPTION

VAPRO SINERGIA FSL 0W-30 has been formulated with special active cleansing technology. It works harder to protect than conventional motor oils by continuously preventing dirt and sludge build-up. In addition to offering excellent engine protection for all driving conditions, **VAPRO SINERGIA FSL 0W-30** cleans and protects to help deliver extra responsiveness.

APPLICATION

VAPRO SINERGIA FSL 0W-30 suitable for fuel-injection gasoline engines with turbocharged. **VAPRO SINERGIA FSL 0W-30** is designed to help deliver outstanding engine protection and fuel economy benefits. **VAPRO SINERGIA FSL 0W-30** is recommended for extreme cold condition to help deliver quick starts and fast lubrication.

PERFORMANCE FEATURES AND BENEFITS

- Special active cleansing technology up to twice as effective at removing sludge from dirty engines as a normal mineral oil.
- Enhanced oxidation stability up to 25% more protection than other synthetic technology leading brands tested.
- Low viscosity, rapid oil flow and low friction greater fuel efficiency and easier cold starting.
- High shear stability maintains viscosity and stays in grade throughout the oil-change interval.
- Specially selected synthetic base oils reduce oil volatility and therefore oil consumption, helping to reduce the need for top-up.
- Minimises vibration and engine noise smoother and quieter drive.

SPECIFICATIONS AND APPROVALS

VAPRO SINERGIA FSL	0W-30
API	SN/CF
ACEA	C2/C3-2012
MB Approval	229.51
VW	502.00/505.01
BMW	BMW Longlife-04

TYPICAL PHYSICAL CHARACTERISTICS

VAPRO SINERGIA FSL		0W-30
SAE Viscosity Grade		0W-30
Density @ 15°C kg/l	ASTM D 4052	0.848
Kinematic viscosity @ 40°C cSt @ 100°C cSt	ASTM D 445 ASTM D 445	63 11.3
Viscosity Index	ASTM D	175
Flash Point °C	ASTM D 92	220
Pour Point °C	ASTM D 97	-42
HTHS Viscosity @ 150°C m PaS	ASTM D 4683	3.0

These characteristics are typical of current production. Whilst future production will conform to Vapro's specification, variations in these characteristics may occur.



SAFETY & PROTECTION

VAPRO SINERGIA FSL 0W-30 oil are unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standards of industrial and personal hygiene are maintained. Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

PROTECT THE ENVIRONMENT

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.