



VAPRO SINERGIA FSL 10W-30

SN

FULLY SYNTHETIC ENGINE OIL

DESCRIPTION

VAPRO SINERGIA FSL 10W-30 is premium automotive motor oil that protects against deposit and sludge formation and provides excellent wear protection to critical engine parts.

APPLICATION

VAPRO SINERGIA FSL 10W-30 is suitable for use in four-stroke gasoline engines used in passenger cars, light trucks, powerboats, motorcycles, and other mobile and stationary equipment. They are excellent for high-revving engines in small cars and light trucks. All grades are suitable for use in turbocharged engines. They may also be suitable for use in natural gas engines in small cars and light trucks after consulting with the appropriate original equipment manufacturer's lubrication recommendations.

PERFORMANCE FEATURES AND BENEFITS

- **VAPRO SINERGIA FSL 10W-30** premium quality automotive engine oils.
- All grades are formulated with high quality base stocks, and robust additive packages including shear-stable viscosity index improvers, detergents, dispersants, anti-wear agents, corrosion inhibitors, antioxidants and foam inhibitors.
- Their anti-wear additives provide excellent wear protection of critical engine parts.
- A high level of dispersancy in **VAPRO SINERGIA FSL 10W-30** protects against deposit and sludge formation in stop-and-go driving, sustained high temperature operation, and protects against corrosion.

SPECIFICATIONS AND APPROVALS

| VAPRO SINERGIA FSL | 10W-30 |
|--------------------|---------|
| API | SN |
| ACEA | A1/B1 |
| Chrysler | MS-6395 |
| GM | 6094M |

TYPICAL PHYSICAL CHARACTERISTICS

| VAPRO SINERGIA FSL | | 10W-30 |
|--------------------------------|-------------|---------------|
| SAE Viscosity Grade | | 10W-30 |
| Density @ 15°C kg/l | ASTM D 4052 | 0.845 |
| Kinematic viscosity @ 40°C cSt | ASTM D 445 | 68.4 |
| @ 100°C cSt | ASTM D 445 | 10.3 |
| Viscosity Index | ASTM D | 137 |
| Flash Point °C | ASTM D 92 | 215 |
| Pour Point °C | ASTM D 97 | -29 |
| HTHS Viscosity @ 150°C m PaS | ASTM D 4683 | 3.0 |

These characteristics are typical of current production. Whilst future production will conform to Vapro's specification, variations in these characteristics may occur.



SAFETY & PROTECTION

VAPRO SINERGIA FSL 10W-30 oil are unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standards of industrial and personal hygiene are maintained. Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

PROTECT THE ENVIRONMENT

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.