

VAPRO SUPER TURBO 15W-40

SN

MULTIGRADE ENGINE OIL

DESCRIPTION

VAPRO SUPER TURBO 15W-40 has been formulated with special active cleansing technology. It works harder to protect than conventional motor oils by continuously preventing dirt and sludge build-up and reduces engine noise.

APPLICATION

VAPRO SUPER TURBO 15W-40 suitable for fuel-injection gasoline engines and diesel engines with turbocharged or supercharged.

PERFORMANCE FEATURES AND BENEFITS

- **VAPRO SUPER TURBO 15W-40** formulated with special cleansing technology up to 20% as effective at removing sludge from dirty engines.
- Good oxidation stability resists oil degradation throughout the oil change interval.
- High shear stability maintains viscosity and stays in grade throughout the oil-change interval.
- High quality base oil helps reduce the oil volatility, helping to reduce the need for top-up.
- Minimises vibration and engine noise smoother and quieter drive.

SPECIFICATIONS AND APPROVALS

API SN
ACEA A3/B3

TYPICAL PHYSICAL CHARACTERISTICS

| VAPRO SUPER TURBO | METHOD | TYPICAL RESULTS |
|--------------------------------|-------------|-----------------|
| SAE Viscosity Grade | SAE | 15W-40 |
| Density @ 15°C kg/l | | 0.875 |
| Kinematic Viscosity @ 40°C cSt | ASTM D 445 | 113.7 |
| @ 100°C cSt | ASTM D 445 | 14.9 |
| Viscosity Index | ASTM D 2270 | 130 |
| Flash point °C | ASTM D 92 | 230 |
| Pour point °C | ASTM D 97 | -30 |

These characteristics are typical of current production. Whilst future production will conform to Vapro's specification, variations in these characteristics may occur.